

IRAS Tempo Grader – for Live fish

ADG0099

Tempo Grader LF 60 type 4/3 (indoor use)

8 pcs. Ø60 mm Roller, Roller length 1500 mm.
4 Tracks, Adjustable 0 – 38 mm, 3 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 200 – 2000 kg fish per hour
Fish size: 1 – 400 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 2900x1115x1460(+240) mm, 345 kg



DG-0024-1

ADG0049

Tempo Grader LF 60 type 4/4 (indoor use)

8 pcs. Ø60 mm Roller, Roller length 2300 mm.
4 Tracks, Adjustable 0 – 38 mm, 4 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 200 – 3000 kg fish per hour
Fish size: 1 – 500 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 3690x1115x1460(+240) mm, 410 kg



DG-0013-100

ADG0143

Tempo Grader LF 60 type 7/4 (indoor use)

14 pcs. Ø60 mm Roller, Roller length 2300 mm.
7 Tracks, Adjustable 0 – 38 mm, 4 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 400 – 6000 kg fish per hour
Fish size: 1 – 500 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 3850x1400x1700 mm, 755 kg



DG-0041-011728

ADG0052

Tempo Grader LF 60 type 10/4 (indoor use)

20 pcs. Ø60 mm Roller, Roller length 2300 mm.
10 Tracks, Adjustable 0 – 38 mm, 4 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 400 – 8000 kg fish per hour
Fish size: 1 – 500 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 3850x2000x1700 mm, 1000 kg



DG-0026-1

ADG0003**Tempo Grader LF 76 type 4/4**

8 pcs. Ø76 mm Roller, Roller length 2300 mm.
Unique sliced Spiral on Rollers
4 Tracks, Adjustable 0 – 45 mm, 4 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 3 – 6 ton fish per hour.
Fish size: 20 – 900 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 3800x1300x1500(+240) mm, 550 kg



DG-0023-1

ADG0005**Tempo Grader LF 76 type 4/4 XL**

8 pcs. Ø76 mm Roller, Roller length 2900 mm.
Unique sliced Spiral on Rollers
4 Tracks, Adjustable 10 – 75 mm, 4 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 4 – 8 ton fish per hour.
Fish size: 30 – 2500 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 5200x1650x1785(+240 / -300) mm, 1000 kg



DG-0005-3

ADG0053**Tempo Grader LF 76 type 7/4 XL**

14 pcs. Ø76 mm Roller, Roller length 2900 mm.
Unique sliced Spiral on Rollers
7 Tracks, Adjustable 10 – 75 mm, 4 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 8 – 16 ton fish per hour.
Fish size: 30 – 2500 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 5300x2270x2350 mm, 1850 kg



DG-0012-105

ADG0152 (New model)**Tempo Grader LF 90 type 6/3**


12 pcs. Ø90 mm Roller, Roller length 2900 mm
Unique sliced Spiral on Rollers
6 Tracks, Adjustable 20 – 120 mm, 3 Grading sizes
Frequency controlled roller speed
Reversible angled outlet. Build-in De-watering system
Capacity 12 – 20 tons fish per hour.
Fish size: 100 – 5000 gr. depending of fish species.
Excl. Non-return flap
LxWxH: 5840x2300x2660 mm, 1985 kg



DG-0042-016652

Option
Upwelling for Iras Tempo Grader – Live fish

The inlet of Iras Tempo Grader for Live fish can be equipped with an upwelling device.



DG-0026-004143

ALF0713
Upwelling DN150 for
Tempo Grader LF 60 4/3, Tempo Grader LF 60 4/4 and Tempo Grader LF 76 4/4

ALF0714
Upwelling DN150 for Tempo Grader LF 60 7/4 and Tempo Grader LF 60 10/4

ALF0715
Upwelling DN200 for Tempo Grader LF 60 7/4 and Tempo Grader LF 60 10/4

ALF0716
Upwelling DN200 for Tempo Grader LF 76 4/4 XL

ALF0717
Upwelling DN250 for Tempo Grader LF 76 4/4 XL

ALF0718
Upwelling DN200 for Tempo Grader LF 76 7/4 XL

ALF0719
Upwelling DN250 for Tempo Grader LF 76 7/4 XL

ALF0720
Upwelling DN250 for Tempo Grader LF 90 6/3

ALF0721
Upwelling DN300 for Tempo Grader LF 90 6/3
